

INTERLEAVING PAPER

200GSM

Interleaving Paper is typically used as a barrier during the pressing operation when manufacturing 'engineered stone'. It is available with three types of coating according to customer requirements to control the penetration of oils into the paper and to improve smoothness properties.

PHYSICAL DIMENSIONS

Physical dimensions are according to customer requirements with a maximum of 3.4m wide.

KEY PROPERTIES

- Good smoothness properties
- Good tensile and tear strength
- Very low porosity

KEY FEATURES & BENEFITS

- A barrier paper
- Three types of barrier coating available to control the penetration of oil
- Manufactured using virgin fibres and recycled fibres



Interleaving Paper

APPLICATIONS

- Engineered stone manufacturing for work tops, counter tops for kitchens and bathrooms
- Replacement of Breton rubber mat systems

TECHNICAL DATA

Property	Test Method	Unit	Typical Value
			22 g/m ²
Thickness		mm	0.170
Tensile Strength	MD	MPa	≥65
Tensile Strength	CD	MPa	≥40
Elongation	MD	%	≥1.5
Elongation	CD	%	≥6.0
Grammage		g/m ²	200
Density		g/cm ³	1.10
Smoothness	W/S	seconds	≥80
Smoothness	F/S	seconds	≥80
Cobb		g/m ²	≥30
Moisture Content		%	≤8.0
Yield		m ² /kg	5.00

Rev. 08.20