

TEMPLATE

A strong and high-performance paper. The product is typically used for making paper patterns for the printing industry (for example on weaving of cloth).

KEY FEATURES & BENEFITS

- High tear strengths
- High ply bond
- High stiffness
- Available in grammages from 200 – 900 gsm

POSSIBLE APPLICATIONS

- Templates & stencils for crafts, industrial manufacturing, & construction
- Shoe and leather production
- Gaskets and seals in industrial machinery & equipment
- Mechanical supports & spacers in manufacturing/assembly



Template Board

STANDARD SIZES

Available Grades	Template Board	Standard Widths
Grammage	200 gsm 300 gsm 630 gsm 820 gsm 900 gsm	widths to suit customer up to 3400 mm (max)

TECHNICAL DATA

Property	Test Method	Unit	Typical Value
			22 g/m²
Thickness		microns	200 ±10%
Tear Strength (Elmendorf)	MD	mN	2000 min
Tear Strength (Elmendorf)	CD	mN	2000 min
Burst strength		kPa	600 min
Stiffness (Taber)	MD	mN	80 min
Stiffness (Taber)	CD	mN	30 min
Grammage		g/m ²	200 ± 5%
Apparent Density		g/cm ³	0.95 - 1.05
Smoothness (Bendsten)	W/S	ml/min	350 max
Smoothness (Bendsten)	F/S	ml/min	350 max
Cobb value		g/m ²	15 - 30
Moisture		%	7.0 max

Rev. 08.23